



SPECIFICATION TEMPLATE

ULTRAPERM Vapour Permeable Membrane – *Item No. UPM15050*

Pliable Building Membrane:

The pliable building membrane shall be ULTRAPERM Deemed-to-Satisfy non-combustible vapour permeable membrane tested in accordance with the latest version of the NCC as per the below technical data and supplied by Blue Chip Group Pty Ltd (Ph: 1300 945 123).

NO ALTERNATIVE MATERIALS WILL BE ACCEPTED FOR THIS PROJECT

ITEM	TEST STANDARD	UNIT	RESULT
DTS Non-combustible – NCC 2022	C2D10(6)(f)	-	Pass*
Flammability Index	AS 1530.2	-	1*
Material Thickness	Actual	mm	0.6*
Material Density	Actual	g/m2	135
Duty / Tensile Strength	AS 1301.448s	kN/m	MD 5.1
Classification = Light Wall		kN/m	LD 3.0
Edge Tear Resistance	AS 4200.1	N (25mm)	MD 251
Classification = Extra Heavy		N (25mm)	LD 155
Dry Delamination	AS 4201.1	-	Pass
Wet Delamination	AS 4201.2	-	Pass
Shrinkage	AS 4201.3	%	-0.1
Water Barrier	AS 4201.4	Both sides	Pass**
Emittance – Black Face	AS 4201.5	Value	0.87
Classification = Non-reflective	AS 4201.5	Reflectance	13%
Emittance – Blue Face	AS 4201.5	Value	0.79
Classification = Non-reflective	AS 4201.5	Reflectance	21%
Vapour Transmission	ASTM E96	g/h.m2	15.18
		g/24h./m2	364.25
Vapour Permeance	ASTM E96	μg/N.s	2.88
Vapour Resistance	ASTM E96	MN.s/g	0.3
Vapour Barrier	ASTM E96	Classification	Class 4***
Burst Force	AS 2001.2.19	N	277
Bursting Strength	AS 4200.1	Classification	Light Wall
Surface Resistivity – Black Face	AS 3100	Megaohms	22.6
Surface Resistivity – Blue Face	AS 3100	Megaohms	21.9
Classification = Non-conductive			

^{*}Deemed-to-satisfy non-combustible as per NCC 2022 clause C2D10(6)(f), with thickness <1mm and Flammability Index <5. **Classified as a 'Water Barrier' as required by NCC 2022 Clauses F3D3 and F8D3(1). ***Classified 'Vapour Permeable, Class 4' for use in all climate zones 1-8 as required by NCC 2022 Clauses F8P1 and F8D3(2).

Installation Instructions: Install and tape in accordance with AS 4200.2 to provide a Deemed-to-Satisfy weatherproofing barrier in accordance with NCC 2022, Clause F3D3.

Product Warranty: Provide a manufacturer's warranty for a minimum period of 10 years. All work is to be carried out in accordance with the manufacturer's recommendations.

ULTRAPERM Draft Specification (V0524) – **Page 1 of 1 Phone:** 1300 945 123 **Email:** sales@bluechipgroup.net.au | <u>Website</u> | <u>Disclaimer</u> | <u>Terms</u>