

# tesa® 60150



## Product Information

### Adhesion Promoter

tesa® 60150 Adhesion Promoter Universal can be used to improve the adhesion of tesa's pressure-sensitive adhesive tapes to various substrates, including zinc, steel and PP/EPDM. It is especially recommended for our ACX<sup>plus</sup> product family. The UV-traceability of our tesa® 60150 Adhesion Promoter allows easy quality control during the application process. Once the substrate has been properly pre-treated with tesa® Adhesion Promoter 60150, the bond should be established within 15 minutes. Tests have proven that the adhesion promoter produces significantly higher peel adhesion values.

### Main Application

\*tesa® 60150 is a liquid used to improve and promote the adhesion of tesa® tape on a range of substrates

\*The adhesion promoter is recommended for various substrates such as PVC, PP/EPDM, ABS, zinc, steel and aluminium

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

|               |              |                      |                        |
|---------------|--------------|----------------------|------------------------|
| • Color       | light-yellow | • Viscosity          | 15 mPa s               |
| • Consistency | liquid       | • Density            | 0.81 g/cm <sup>3</sup> |
| • Solids      | 7 %          | • Spreading rate ca. | 15 m <sup>2</sup> /l   |

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=60150>