

# tesa® 51495 PV2



## Product Information

### Reinforced Aluminum Foil Tape

tesa® 51495 PV2 consists of aluminium foil reinforced with polyethylene scrim which is coated with a synthetic rubber based adhesive.

#### Features:

- Release liner for ease of unwind
- Vapor barrier
- Heat and radiation reflective properties
- Excellent adhesion to own backing
- High bond strength
- Suitable for operating temperatures from -20°C to 80°C

### Main Application

- Joining roofing and wall insulation
- Wrapping of pipes
- Sealing air conditioning ducts

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	aluminium foil	• Tensile strength	46 N/cm
• Color	silver	• Type of liner	flat white silicone paper
• Total thickness	205 µm	• Temperature resistance min.	-20 °C
• Type of adhesive	synthetic rubber	• Temperature resistance max.	80 °C
• Elongation at break	25 %		

#### Adhesion to

- steel 9.0 N/cm

# tesa® 51495 PV2



## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=51495>