



INSULBLUE

Foam Insulation

Description

INSULBLUE foam insulation products are a heavy duty 3-in-1 insulation, thermal and radiant barrier comprising of an advanced high density closed cell XPE foam material sandwiched between two layers of poly woven foil. INSULBLUE foam insulation provides excellent thermal properties and reflectivity and is suitable for use in roof, cavity, wall wrap and floor systems for all construction types. It provides superior thermal ratings to standard sarking and helps to reduce thermal bridging between building elements such as exterior cladding and structure.

Product Benefits



EASY TO USE

INSULBLUE foam insulation is a ultra flexible product which is easily adaptable for wraparound areas and varied surface types making it quick and easy to install.



BCA COMPLIANT

FIBRE-FREE MATERIAL

contractors to work with.

INSULBLUE foam insulation has been tested in accordance with relevant Australian standards giving confidence to builders and contractors for suitability in all applications.

Made from cross-linked closed cell XPE foam,

INSULBLUE foam insulation is non-irritant

to skin and non-allergenic making it easy for



TEAR RESISTANCE

performance.

With heavy duty foil and high density XPE foam core, INSULBLUE foam insulation is able to withstand high wind and has high tear resistance in extreme conditions.



CLEAR CAVITY MAINTAINED When INSULBLUE foam insulation is used in wall cavity applications such as double brick construction a clear cavity is still maintained making it easily accessible for services.



PROVEN TO PERFORM IN WA

RESISTANT TO DELAMINATION

over time ensuring excellent long term

The poly woven reflective foils used in the

manufacture of INSULBLUE foam insulation

offer outstanding resistance to delamination

Used widely in roofing, wall wrap and cavity applications across Western Australia, INSULBLUE foam insulation has been proven to withstand the harsh climate statewide.



WATER RESISTANT

The heavy duty facings and closed-cell material structure of INSULBLUE foam insulation means there is no product degradation over time caused by any event of moisture ingress.

Availability

CODE	R-VALUE	DESCRIPTION	LEAD TIME	MOQ
IFX413522	R0.10	INSULBLUE 4mm Foam Insulation, 1.35 x 22.25m	Stock	1 Roll
IFX613522	R0.17	INSULBLUE 6.5mm Foam Insulation, 1.35 x 22.25m	Stock	1 Roll
IFX813522	R0.20	INSULBLUE 8mm Foam Insulation, 1.35 x 22.25m	Stock	1 Roll
IFS813522	R0.20	INSULBLUE 8mm Vapour Barrier, 1.35 x 22.25m	Stock	1 Roll

Accessories

CODE	DESCRIPTION	LEAD TIME	моа
ICS6060	INSULBLUE 60 x 60 x 20mm Cavity Spacers, 50 Pack	Stock	1 Pack
ITP4850	INSULTAPE 48mm Reinforced Foil Tape, 50m Roll	Stock	1 Roll
ITP7250	INSULTAPE 72mm Reinforced Foil Tape, 50m Roll	Stock	1 Roll
ITP9650	INSULTAPE 96mm Reinforced Foil Tape, 50m Roll	Stock	1 Roll

Technical Data

TEST ITEM	STANDARD	RESULT
Thermal Conductivity	ASTM C518	0.04 W/mK
Flammability Index	AS 1530.2	< 5
Spread of Flame Index	AS 1530.3	0
Smoke Developed Index	AS 1530.3	1
Strength / Duty	AS 4200.1	Heavy Duty
Emittance	AS 4201.5	0.03
Reflectivity	Actual	97%
Dry Delamination	AS 4201.1	Pass
Wet Delamination	AS 4201.2	Pass
Corrosion Resistance	AS 4859.1	Pass

INSTALL & TECHNICAL

For installation and technical information, scan the QR code and view 'Downloads' tab.











We've Got It Covered

















Blue Chip Group Pty Ltd

SYDNEY | MELBOURNE | BRISBANE | PERTH P 1300 945 123

E sales@bluechipgroup.net.au

www.bluechipgroup.net.au

DISCLAIMER No information or advice contained in this publication is binding in any way shape or form and is provided on a without prejudice basis. All photographs and colour swatches are indicative only. All dimensions are nominal and all product data and specifications are subject to change without notice. All pricing, sales, communications and transactions are subject to Blue Chip Group's terms of trading which are available on request.