



BLUECHIP

Insulation Products

IROCK

Product Brochure

www.bluechipgroup.net.au



IROCK

Rockwool Insulation Board

Description

IROCK rockwool insulation board is a non-combustible thermal and acoustic insulation material widely used in both external and internal wall applications that require high levels of fire safety and thermal performance. IROCK is manufactured by spinning a molten mixture of natural rock materials and other additives to create fine wool-like fibres which are bonded together using a thermoset resin to form a rigid insulation board. Compliant with NCC 2019 & NCC 2022, IROCK offers excellent long-term ageing performance and superior resistance to water absorption compared to other common insulation materials.

Product Benefits



NON-COMBUSTIBLE

IROCK is deemed non-combustible when tested to AS 1530.1 meaning it is compliant for use in external walls and cladding systems which are required to be non-combustible in buildings of types A & B construction.



COST EFFECTIVE

With a nominal thermal conductivity of 0.036 W/mK and a very economical price-point, IROCK offers excellent thermal efficiency for minimal upfront cost along with life-cycle energy savings for the building.



MOISTURE RESISTANT

Although it is not suitable for permanent immersion or exposure to drenching, IROCK insulation board's thermal performance will not be adversely effected by condensation or contact with liquid water.



ENVIRONMENTALLY FRIENDLY

Largely manufactured from recycled materials and natural rock, IROCK is environmentally friendly as an initial product. It also offers numerous environmental benefits in application as thermal insulation.



EXCELLENT ACOUSTIC PERFORMANCE

Along with excellent fire safety and thermal performance, IROCK also provides an excellent acoustic performance of NRC >1.0 in accordance with ISO 354-2006 providing an ideal solution for party walls.



NCC 2022 COMPLIANT

NCC 2022 Clause C2D10 specifically requires all components of external walls including cladding, insulation and framing to be non-combustible and IROCK is one of only a few materials that meet this criteria.



LIGHT-WEIGHT & DURABLE

IROCK rockwool insulation boards are both light-weight and highly durable for easy hassle-free handling onsite and they can be easily cut and formed to suit almost any application.



SUPERIOR AGEING PERFORMANCE

Unlike low density batts which tend to slump in vertical applications or PIR and phenolic insulation which lose thermal performance over time, IROCK is anti-slump and has excellent long-term ageing performance.

Availability

| CODE | R-VALUE | DESCRIPTION | LEAD TIME | MOQ |
|-----------|---------|--|------------|---------------------|
| R301206 | R0.83 | IROCK 30mm Rockwool Board, 100 x 600mm | 8-10 Weeks | 2,160m ² |
| IR401206 | R1.11 | IROCK 40mm Rockwool Board, 1200 x 600mm | Stock | 8 Boards |
| IR501206 | R1.39 | IROCK 50mm Rockwool Board, 1200 x 600mm | 8-10 Weeks | 1,368m ² |
| IR601206 | R1.67 | IROCK 60mm Rockwool Board, 1200 x 600mm | Stock | 5 Boards |
| IR801206 | R2.22 | IROCK 80mm Rockwool Board, 1200 x 600mm | Stock | 4 Boards |
| IR1001206 | R2.78 | IROCK 100mm Rockwool Board, 1200 x 600mm | 8-10 Weeks | 648m ² |

Technical Data

| TEST ITEM | STANDARD | RESULT |
|-----------------------------|--------------|-----------------------|
| Thermal Conductivity | ASTM C518 | 0.036 W/mK |
| Acoustic Performance | ISO 354-2006 | 1.0 NRC |
| Non-combustible (DtS) | AS 1530.1 | Pass |
| Ignitability Index | AS 1530.3 | 0 |
| Spread of Flame Index | AS 1530.3 | 0 |
| Heat Evolved Index | AS 1530.3 | 0 |
| Smoke Developed Index | AS 1530.3 | 0-1 |
| Material Density | Actual | 100 kg/m ³ |
| Compressive Strength | ASTM C165-07 | 10 KN/m ² |
| Maximum Service Temperature | Actual | <750°C |
| Melting Temperature | Actual | >1000°C |
| Rockwool Content | Actual | >95% |
| Resin Content | Actual | <5% |
| Water Absorption | EN 1609 | <1.1% |
| Fungal Resistance | ASTM C655 | Pass |

INSTALL & TECHNICAL

For installation and technical information, scan the QR code and view 'Downloads' tab.





We've Got It Covered

V0522



Blue Chip Group Pty Ltd
SYDNEY | MELBOURNE | PERTH
P 1300 945 123
E sales@bluechipgroup.net.au

www.bluechipgroup.net.au

DISCLAIMER No information or advice contained in this publication is binding in any way shape or form and is provided on a without prejudice basis. All photographs and colour swatches are indicative only. All dimensions are nominal and all product data and specifications are subject to change without notice. All pricing, sales, communications and transactions are subject to Blue Chip Group's terms of trading which are available on request.