



# Metal Cladding

www.bluechipgroup.net.au

## METAL CLADDING





2 ULTRACORE Non-combustible Aluminium

Core Panel

8 ULTRABOND **Composite Panel** 

## FROM THE STRUCTURE OUT, WE'VE GOT IT COVERED

BLUECHIP specialises in the manufacture and supply of exterior architectural products from the structure out. Our range includes; all types of cladding, decking materials, engineered fixing systems and insulation products. BLUECHIP has now supplied more than 3,000,000m<sup>2</sup> of materials to Australian projects since 2003.



# 20 ULTRALIGN Battens





**Fire Resistant Aluminium** 





12 ULTRASURE Prefinished Solid Aluminium Panel

# **ULTRACORE**

## **Non-combustible Aluminium Core Panel**

### Description

ULTRACORE manufactured by BLUECHIP is a Deemed-to-Satisfy (DtS) non-combustible aluminium panel when tested to AS 1530.1 and AS 1530.3 as per the requirements of the NCC 2019, Clause C1.9(e) (vii). It has also been tested by Exova Warringtonfire to BS 8414 and AS 5113 full-scale testing, proving it does not contribute to the spread fire. Visually, ULTRACORE aluminium core panel looks the same as traditional aluminium composite panel but with zero combustible core content (0%) meaning it achieves the lowest risk rating, category D, from the Insurance Council of Australia.

### **Product Benefits**



#### **PROVEN V-GROOVE DURABILITY**

Unlike SOLID aluminium panels, ULTRACORE can demonstrate 40 years of proven corner durability when using the common v-groove folding system. This is because the front skin is not impacted when v-grooving.



#### AS 1530.1 NON-COMBUSTIBLE

ULTRACORE is one of the few aluminium panels globally that is Deemed-to-Satisfy non-combustible when tested to AS 1530.1 and AS 1530.3 in accordance with the NCC 2019 Clause C1.9(e)(vii) requirements.



#### AS 5113 FIRE TESTING

ULTRACORE is Deemed-to-Satisfy noncombustible so does not require further testing. However it has been tested to AS 5113 fullscale testing by Exova Warringtonfire, proving it does not contribute to the spread of fire.



#### ZERO POLYETHYLENE (0%)

Unlike most other aluminium panel products including FR, Plus, A2 and NC type panels, the ULTRACORE aluminium core panel contains ZERO percent flammable polyethylene (0%) and each lamina is 100% non-combustible.



ULTRACORE aluminium core panel has thermal conductivity of 2.54 W/mK compared to 205 W/mk for SOLID aluminium panel. This means 80x less heat transfer into the building for greater fire safety and section J compliance.

#### FASTER FABRICATION TIME



Compared to solid aluminium panel, ULTRACORE panel is much more cost-effective, faster and easier to fabricate on CNC machines using the well-proven z-angle cassette system with concealed mechanical fixings.

#### **OIL-CANNING RESISTANCE**

Oil-canning is the uneven distribution of tension in SOLID aluminium panels which results in a rippling effect on the facade. The superior mechanical properties of ULTRACORE guarantees against oil-canning.

#### LESS CARBON FOOTPRINT



ULTRACORE aluminium core panel uses approximately 50% less aluminium per m2 than SOLID aluminium panels for much less carbon footprint and it is 50% lighter for signifigant structural and labour savings.

### **Product Range**




Availability

Solid / Matt Colours

DECODIDION			MOO
DESCRIPTION	SHEET SIZES	LEAD TIME	MOQ
ULTRACORE Metallic Stock Colours UC9701, UC9205, UC9134, UC9137, UC9308, UC4150, UC5292, UC9809	2500, 3200, 4000 x 1500mm	Stock	1 Sheet
ULTRACORE Solid Stock Colours UC1005, UC1025, UC9902, UC1255, UC1270, UC9130, UC1590, UC1460, UC1140, UC1190, UC1677	2500, 3200, 4000 x 1500mm	Stock	1 Sheet
ULTRACORE Non-stock, BCG & Custom Colours	2500, 3200, 4000 x 1250mm 2500, 3200, 4000 x 1500mm	8-10 Weeks	300m²
ULTRACORE Matt, Sparkling, Chromatic & Imitation Colours	2500, 3200, 4000 x 1250mm 2500, 3200, 4000 x 1500mm	8-10 Weeks	300m²

### System Components





STUDTEK Steel Sub-framing

EXTRUSIONS Z-angles & Trims


#### **INSTALL & TECHNICAL**

For installation and technical information, scan the QR code and view 'Downloads' tab.





AS 1530.1 Sarking










Sparkling Colours



Chromatic Colours



UITRACORE Imitation Finishes





TAPES & GASKETS Foil & Foam Tapes



JOINT SEALANT Prolastik & Sikaflex

# ULTRACORE

## **Colour Chart**

(s) after colour names indicates stock colours. All other colours require lead times and minimum order quantities.





### Solid Colours

Metallic

(s)





**BCG** Colours






#### UNLIMITED CUSTOM COLOURS



ULTRACORE has unlimited colour options, we are able to match any colour from any other colour range. With small MOQ's and fast lead times you can realise your vision.



# ULTRACORE

## **Colour Chart**

### Matt Colours




### Sparkling Colours



# **Chromatic Colours**





### **Timber Imitations**



### **Stone Imitations**



Pearl White

Cashmir Beige Beige

UC6305 Travertine Atlas Travertine Calico Cream

### **Metal Imitations**





Brushed Silver Dark UC5260 Zinc Charcoal

UC5150 Brushed Copper



#### UNLIMITED CUSTOM COLOURS

ULTRACORE has unlimited colour options, we are able to match any colour from any other colour range. With small MOQ's and fast lead times you can realise your vision.







UC8385 Ascot Teak



UC8650 Noble Bloodwood



UC8395 Polished Rengas



UC6310 Granite UC6280 Aurisina Beige



Granite Magenite Black

# **ULTRABOND**

## **Fire Resistant Aluminium Composite Panel**

### Description

ULTRABOND is a 4mm thick fire resistant aluminium composite panel comprising of a >70% mineral filled core, sandwiched between two prefinished aluminium or other natural metal cover sheets such as zinc, copper or stainless steel. Utilising the reknowned PVDF paint system, ULTRABOND aluminium composite panel has been thoroughly tested in Australia by NATA accredited CSIRO and Exova Warringtonfire and is manufactured to the highest quality standards. It is also BCA/NCC compliant for all type C\* construction projects and has full-scale fire testing in accordance with AS 5113.

### **Product Benefits**

ULTRABOND fire resistant aluminium composite panel is compliant with NCC 2019 for use as external cladding on all type C\* construction projects ensuring you are specifying a compliant

# product tested to Australian standards.

#### **PVDF PAINT SYSTEM**

ULTRABOND fire resistant aluminium composite panel only uses the highly recognised PVDF Kynar 500 or FEVE paint systems known for their high durability and optimum resistance to weather and industrial pollution.

#### LOW MAINTENANCE



**AS 5113 FIRE TESTING** Although not required for type C construction, ULTRABOND fire resistant aluminium composite panel has been tested to AS 5113 by NATA approved Exova Warringtonfire to prove it does contribute to the spread of fire.



### UNLIMITED CUSTOM COLOURS

NCC 2019 COMPLIANCE

ULTRABOND fire resistant aluminium composite panel has unlimited colour options, we are able to match any colour from any other colour range. With small MOQ's and fast lead times you can realise your vision.



### LOCAL STOCK AVAILABLE

ULTRABOND fire resistant aluminium composite panel is stocked in a range of standard solid colours and metallic colours for fast delivery at all times.



The ULTRABOND FR fire resistant aluminium composite panel finish has undergone 40+ years of exposure testing which is continuing to confirm the superior properties of fluoropolymer coatings.

#### COST EFFECTIVE



ULTRABOND fire resistant aluminium composite panel has enjoyed consistent growth not only due to the desire for a clean and modern look, but also a product offering rapid cost effective installation.

#### FULL WARRANTY



ULTRABOND fire resistant aluminium composite panel has a long track record of consistency, reliability and quality allowing us to offer up to 15 year's warranty when installed by a licensed installer

\*For types A & B construction, use ULTRACORE non-combustible aluminium core panel - see page 2.

### **Product Range**





ULTRABOND Solid Colours

### Availability

DESCRIPTION	SHEET SIZES	LEAD TIME	MOQ
ULTRABOND Metallic Stock Colours UB9701, UB9205, UB9134, UB9137, UB9308	2500, 3200, 4000 x 1570mm	Stock	1 Sheet
ULTRABOND Solid Stock Colours UB1005, UB9130, UB1677	2500, 3200, 4000 x 1570mm	Stock	1 Sheet
ULTRABOND Non-stock, BCG & Custom Colours	2500, 3200, 4000 x 1250mm 2500, 3200, 4000 x 1570mm	8-10 Weeks	300m²
ULTRABOND Natural Metal Finishes	2500, 3200, 4000 x 1220mm	8-10 Weeks	300m <sup>2</sup>

### System Components





AS 1530.1 Sarking

STUDTEK Steel Sub-framing

EXTRUSIONS Z-angles & Trims

#### **INSTALL & TECHNICAL**

For installation and technical information, scan the QR code and view 'Downloads' tab









Metallic Colours

ULTRABOND Natural Zinc







ULTRABOND Natural Copper



UITRABOND **Mirror Stainless** 





TAPES & GASKETS Foil & Foam Tapes



JOINT SEALANT Prolastik & Sikaflex

# ULTRABOND

## **Colour Chart**

(s) after colour names indicates stock colours. All other colours require lead times and minimum order quantities.





### Solid Colours



### **BCG Colours**




### BGC Colours Cont'd



### Natural Metal Finishes






Grey Zinc Zinc

UB5160 Natural Copper

UB5800 Stainless Steel Mirror





# **ULTRASURE**

## **Prefinished Solid Aluminium Panel**

### Description

Designed to compliment our ULTRACORE non-combustible core panel, ULTRASURE completes our range of BCA compliant, Deemed-to-Satisfy non-combustible aluminium cladding solutions. The 3mm solid aluminium cladding panels offer very high impact resistance and can be curved, rolled or perforated. ULTRASURE features the same factory applied PVDF coating system widely renowned for its superior durability and finish quality. Unlike traditional powder coating, prefinished PVDF panels do not require fabrication prior to coating greatly reducing lead-times and costs.

### **Product Benefits**



#### FINISHED BEFORE FABRICATION

AS 1530.1 NON-COMBUSTIBLE

of NCC 2019 Clause C1.9(e)(v).

NCC 2019 COMPLIANCE

C construction.

ULTRASURE is one of the few aluminium

cladding panel solutions that is Deemed-to-

Satisfy non-combustible when tested to AS 1530.1 and AS 1530.3 as per the requirements

ULTRASURE solid aluminium panel is Deemed-

to-Satisfy non-combustible as per NCC 2019

Clause C1.9(e)(v) making it compliant for use as

external cladding on any project of types A, B &

Unlike traditional powder coated panels, ULTRASURE is prefinished with factory applied PVDF coating and a protective peel-off film before fabrication into cladding panels providing many practical advantages.



#### COLOUR-MATCHED FIXINGS

BLUECHIP does not endorse installing any brand of SOLID aluminium panels with the v-grooved cassette system - it is flawed methodology which will likely lead to future cracking and water ingress issues.



#### **PVDF PAINT SYSTEM**



ULTRASURE 3mm aluminium panel only uses the highly recognises PVDF KYNAR 500 or FEVE paints known for their high durability, providing the optimum resistance to weather and industrial pollution.

#### CURVE, ROLL OR PERFORATE

The ULTRASURE 3mm aluminium panel offers excellent design versatility as it can be made into panels of almost any shape and size as well as being suitable for curved panels, rolling and perforating.

#### MANUFACTURER'S WARRANTY




UNLIMITED CUSTOM COLOURS ULTRASURE 3mm solid aluminium panel utilises the same PVDF coating as ULTRABOND FR and ULTRACORE so it is available in the same extensive colour range and custom colours. MOQ's apply.



ULTRASURE 3mm aluminium panel coating system has a long track record of consistency, reliability and quality allowing us to offer up to 15 year's warranty when installed by a licensed installer.

### **Product Range**



ULTRASURE

Availability

DESCRIPTION	SHEET SIZES	LEAD TIME	ΜΟQ
ULTRASURE Metallic Colours	2500, 3200, 4000 x 1500mm	10-12 Weeks	1200m²
ULTRASURE Solid Colours	2500, 3200, 4000 x 1500mm	10-12 Weeks	1200m <sup>2</sup>
ULTRASURE Non-stock, BCG & Custom Colours	2500, 3200, 4000 x 1250mm 2500, 3200, 4000 x 1500mm	10-12 Weeks	1200m <sup>2</sup>
ULTRASURE Metal Imitation Finishes	2500, 3200, 4000 x 1250mm 2500, 3200, 4000 x 1500mm	10-12 Weeks	1200m²

### System Components

Steel Sub-framing



FIRESPAN AS 1530.1 Sarking COLOURFIX **Coloured Fixings** 

#### **INSTALL & TECHNICAL**

For installation and technical information, scan the QR code and view 'Downloads' tab.









Metal Imitations





TAPES & GASKETS Foil & Foam Tapes



JOINT SEALANT Prolastik & Sikaflex

# ULTRASURE

## **Colour Chart**

### **Metallic Colours**



### Solid Colours



### **BCG Colours**



BGC Colours Cont'd



### Metal Imitations




Brushed Silver Brushed Copper



#### UNLIMITED CUSTOM COLOURS

ULTRASURE has unlimited colour options, we are able to match any colour from any other colour range. With small MOQ's and fast lead





US8008 Olive Brown

US8028 Terra

Brown



US8019 Grey Brown



US4007 Purple Violet



US3020 Traffic US3001 Signal US3003 Ruby US3005 Wine Red



Red



Red



Red


# ULTRANAMEL

## Vitreous Enamel Panel

### Description

ULTRANAMEL vitreous enamel panel consists of a highly durable vitreous enamel coating applied to a decarbonised steel panel with an aluminium honeycomb or calcium silicate backing sheet. Vitreous enamelled architectural panels are routinely specified for commercial, institutional and infrastructure projects around the world; perfect for high impact, high traffic areas such as train stations, shopping malls and tunnels. ULTRANAMEL vitreous enamel panel has excellent anti-graffiti properties and is non-combustible providing unrivalled performance in public areas.

### **Product Benefits**



ULTRANAMEL vitreous enamel panel is available in an almost unlimited colour range. The original colour of the vitreous enamel panel is extremely durable and is expected to outlast a normal building life.



#### **GRAFFITI PROOF**

ULTRANAMEL vitreous enamel panel is extremely durable. The vitreous enamel coating has excellent scratch, graffiti and impact resistance making it ideal for areas of heavy traffic or extreme wear.



#### **UV RESISTANT**

ULTRANAMEL vitreous enamel panel has a far superior colour consistency over time when compared to typical cladding panels. The colour and gloss level of these panels are unaffected by sunlight.



#### **FAST INSTALLATION**

ULTRANAMEL vitreous enamel panel is manufactured to order from provided shop drawings. The panels are formed into premade cassettes with fixing clips ready for fast and easy onsite installation.

#### NON-COMBUSTIBLE



ULTRANAMEL vitreous enamel panel is a completely deemed-to-satisfy non-combustible steel cladding system in accordance with NCC 2019 C1.9(e)(vii), withstanding temperatures of over 400°C and are able to provide fire ratings of over 2 hours.

#### LOW MAINTENANCE



ULTRANAMEL vitreous enamel panel is very low maintenance. The surface is completely impervious to contaminants, extremely smooth and extremely low static, preventing dust adhesion and resulting in only minimal cleaning required.

#### VERSATILE DESIGN



ULTRANAMEL vitreous enamel panel can be custom designed into a wide range of shapes and dimensions. This compiled with a vast colour range make ULTRANAMEL a versatile design choice.


#### HYGIENIC SURFACE



ULTRANAMEL vitreous enamel panel has a completely non-porous surface that does not absorb any bacteria. The non-stick surface allows intense cleaning with hospital grade cleaning agents.

### **Product Range**





L-shaped Panels

### Availability

DESCRIPTION	PANEL SIZES	LEAD TIME	ΜΟQ
ULTRANAMEL Flat Panels	Custom Sizes up to 2400 x 1150mm	10-12 Weeks	1 Panel
ULTRANAMEL L-shaped Panels	Custom Sizes up to 1600 x 1150m (1150mm is Width + Return)	10-12 Weeks	1 Panel
ULTRANAMEL U-shaped Panels	Custom Sizes up to 1600 x 1150m (1150mm is Width + Both Returns)	10-12 Weeks	1 Panel
ULTRANAMEL Curved Panels	Custom Sizes up to 1600 x 1150m (1150mm is Curved to Min. 300mm Radius)	10-12 Weeks	1 Panel

### System Components



FIRESPAN AS 1530.1 Sarking SINIAT WD **Rigid Air Barrier** 



#### **INSTALL & TECHNICAL**

For installation and technical information, scan the QR code and view 'Downloads' tab.












UITRANAMEI U-shaped Panels



UITRANAMEI **Curved Panels** 





NVELOPE Aluminium Framing



SEALANTS Prolastik & Sikaflex

# ULTRANAMEL

## **Colour Chart**

**BCG Colours** 



### BGC Colours Cont'd



#### UNLIMITED CUSTOM COLOURS



ULTRANAMEL has unlimited colour options, we are able to match any colour from any other colour range. With small MOQ's and fast lead times you can realise your vision.







UN8008 Olive UN8028 Terra UN8019 Grey Brown



Brown



Brown



UN4007 Purple Violet



UN3020 Traffic UN3001 Signal UN3003 Ruby UN3005 Wine Red



Red



Red



Red



# **ULTRALIGN**

## **Aluminium Cladding & Battens**

### Description

ULTRALIGN intelligent aluminium facade system is available in a range of solid aluminium profiles providing a reliable and attractive modern facade alternative to other commercial cladding products. ULTRALIGN products have been specifically designed by experienced commercial facade professionals to meet the demands of today's facade industry. Australian made using the finest raw materials and finish options, ULTRALIGN offers an unprecedented level of quality, reliability, and longevity with an extensive range of colours, textures, and finish options, available in both standard and custom sizes.

### **Product Benefits**



#### AS 1530.1 NON-COMBUSTIBLE

ULTRALIGN products are made of 100% solid aluminium which is totally non-combustible to AS 1530.1. Architects, engineers, and tenants can be assured ULTRALIGN will not burn or contribute to fire spread.



### INTELLIGENT INSTALLATION

The ULTRALIGN profile has been intelligently designed to provide excellent usability such as multi-angle mating and it has one single swarffree contact point for superior consistency and weather-proofing.



#### PREFINISHED SYSTEM

The entire ULTRALIGN range is pre-finished. This means there is no requirement for painting or onsite finishing. Our finish options are attractive and durable - guaranteed to stand the test of time.



#### 100% AUSTRALIAN MADE

ULTRALIGN is a 100% Australian owned, designed and made product, which contributes to it's outstanding quality and fast lead times. Using ULTRALIGN aids all aspects of the Australian economy



'nΖ



product. Energy, emissions, wastage and materials are saved in every aspects of the product from manufacturing, to, delivery, installation and recycling.

#### MINIMAL FABRICATION



ULTRALIGN panels can be ordered to custom lengths which eliminates additional fabrication. Panels are simply interlocked and tightened, then fixed. This also optimises usability and decreases waste.

#### **INCREDIBLE AESTHETICS**



ULTRALIGN profiles all have their own unique look with classic shadow lines, sharp step features or bold standing seams. Add in any anodised, powdercoat or wood grain finish and the options are limitless.

#### INDUSTRY LEADING WARRANTY



ULTRALIGN's 20 year product warranty is one of the longest of any facade product on the market today. Clients can be confident that their facade will remain attractive and durable for years to come.


#### **INSTALL & TECHNICAL**

For installation and technical information, scan the QR code and view 'Downloads' tab.





### Profiles



### Availability

CODE	DESCRIPTION	LEAD TIME	ΜΟQ
UL*G15518	ULTRALIGN 155 x 18mm Groove (Colour), 6.5m Length	2-3 Weeks	1 Length
UL*C20530	ULTRALIGN 205 x 30mm Cabin (Colour), 6.5m Length	8-10 Weeks	50 Lengths
UL*S20548	ULTRALIGN 205 x 48mm Seam (Colour), 6.5m Length	8-10 Weeks	50 Lengths
UL*BXXX50	ULTRALIGN XXX x 50mm Batten (Colour), 6.5m Length	2-3 Weeks	1 Length
ULEXXX50	ULTRALIGN XXX x 50mm Batten End Cap (Colour)	2-3 Weeks	1 End Cap

(\*) The asterix in the code denotes the specified type of finish to be applied to the aluminium extrusion as follows; U = Ultrawood Timber Colours, A = Anodised Colours and P = Powdercoat Colours.

### System Components





FIRESPAN AS 1530.1 Sarking

CLADTRIM Steel Sub-framing Colour-match Trims

Specification Code: UL\*G155 ULTRALIGN Groove Profile Specification Code: UL\*C205 ULTRALIGN Cabin Profile Specification Code: UL\*S205 ULTRALIGN Seam Profile Specification Code: UL\*B5050 ULTRALIGN 50 x 50 Batten **Specification Code:** UL\*B10050 ULTRALIGN 100 x 50 Batten Specification Code: UL\*B15050 ULTRALIGN 150 x 50 Batten Specification Code: UL\*B20050 ULTRALIGN 200 x 50 Batten Specification Code: UL\*B25050 ULTRALIGN 250 x 50 Batten Specification Code: UL\*B30050 ULTRALIGN 300 x 50 Batten





ADHESIVES SikaTack & 11FC



FASTENERS **Cladding Fixings** 

# ULTRALIGN

## **Colour Chart**

### **Anodised Colours**



### **Material Colours**

				4.4	ALC: NO		
UL1602 Pale Brushed	UL1616 Pale Polished	UL1614 Pale Natural	UL0702 Grey Brushed	UL0716 Grey Polished	UL0714 Grey Natural	UL0102 Authentic Brushed	UL0116 Authentic Polished
UL0114 Authentic Natural	UL1618 Pale Rust	UL0318 Coral Rust	UL0118 Authentic Rust	UL2118 Uluru Rust	UL0418 Dark Rust	UL2102 Uluru Brushed	UL2116 Uluru Polished
an and			New Contest				

UL0202 Bronze UL1502 Ochre UL1514 Ochre

Natural

Brushed

### Powdercoat Excel Colours



GN231A Night Sky Matt



UL2114 Uluru Natural

Brushed



Surfmist Matt



Headland Matt Red Matt



GK203A



GK274A Matt







GL210A



GK030A Hawthorn Green Gloss





GG262A Manor GM234A Terrain GL205A Matt



GJ203A Deep GL229A Ocean Matt



GK044A Heritage Green Charcoal Gloss Gloss



Matt



Woodland Matt



Monument Matt



GL035A

# **ULTRALIGN**

## **Colour Chart**

### **Powdercoat Living Colours**



**Powdercoat Vivica Colours** 




### **Precis Colours**




GY21AA Natural GY20BA Dark Shimmer Matt Bronze Matt



### Powdercoat Anodic Colours




### **Powdercoat Sable Colours**



### **Powdercoat Ultriva Colours**



### Powdercoat Vitality Colours



Matt



Champagne Matt



Bronze Satin



Dark Grey Matt



Bass



Black





Eternal Silver Satin



YY22BA Precis Pure Gold Matt



YY377A Sable Brilliance



YY20BA Precis Dark Bronze Matt



YY263A Titanium Pearl Matt



Green Gloss



GK043A Shamrock Green Gloss



Blue Gloss



Satin





#### Blue Chip Group Pty Ltd SYDNEY | MELBOURNE | PERTH P 1300 945 123 E sales@bluechipgroup.net.au

#### www.bluechipgroup.net.au

DISCLAIMER No information or advice contained in this publication is binding in any way shape or form and is provided on a without prejudice basis. All photographs and colour swatches are indicative only. All dimensions are nominal and all product data and specifications are subject to change without notice. All pricing, sales, communications and transactions are subject to Blue Chip Group's terms of trading which are available on request.